SENSORS AND ACTUATORS A VOLUME 42, NUMBERS 1–3, APRIL 15, 1994

Contents

POSTERS

Physical Sensors

Intelligent sensor for monitoring freight-waggon working conditions 347
A. von Jena, B. Fischer, V. Mágori (Munich, Germany) and W. Talke (Braunschweig, Germany)

Integrated 3-D magnetic vector sensor 354
Ch.S. Roumenin (Sofia, Bulgaria)

MIS sensor for investigation of mechanical properties of metals 358
A.P. Babichev, N.E. Babulevich, S.D. Lazarev and S.S. Yakimov (Moscow, Russian Federation)

Optimization of a compact force-sensor/load-cell family 362
K. Bethe (Braunschweig, Germany)

Self-compensating piezoresistive pressure sensor 368
J. Dziuban, A. Górecka-Drzazga, U. Lipowicz, W. Indyka (Wrocław, Poland) and J. Wąsowski (Warsaw, Poland)

Triple-beam resonant silicon force sensor based on piezoelectric thin films 375
Th. Fabula, H.-J. Wagner, B. Schmidt (Villingen-Schwenningen, Germany) and S. Büttgenbach (Braunschweig, Germany)

Heat-flux sensor 381
A. Medvíd' and J. Kaupužs (Riga, Latvia)

Acoustic wave devices to measure gas flow: comparison between surface acoustic wave (SAW) and shear horizontal acoustic plate mode (SH-APM) oscillators 384
D. Rebière, C. Déjous, J. Pistré, J.-L. Aucouturier (Talence, France), C. Tiret and R. Planade (Vert-Le-Petit, France)

Design and fabrication of resonating AT-quartz diaphragms as pressure transducers 389
H.-J. Wagner (Villingen-Schwenningen, Germany), W. Hartig (Leonberg, Germany) and S. Büttgenbach (Braunschweig, Germany)

Magnetic sensors for industrial and field applications 394
P. Ripka (Prague, Czech Republic)

Low-cost high-sensitivity integrated pressure and temperature sensor 398
P. Pons and G. Blasquez (Toulouse, France)

A model for designing an electrical network to increase the speed of pyroelectric sensors 402
L. Capineri, S. Rocchi (Florence, Italy), P. Mazzinghi (Perugia, Italy), M. Rineri and L. Masotti (Florence, Italy)

PVDF ultrasonic sensors for location of small objects 406
A.S. Fiorillo (Fisciano, SA, Italy)

An integrated sensor head in silicon for contactless detection of torque and force 410
P. Rombach and W. Langheinrich (Darmstadt, Germany)

A very low-cost pressure sensor with extremely high sensitivity 417
C. Császár, G. Harsányi (Budapest, Hungary) and R.P. Agarwal (Roorkee, India)

Piezoelectric micromovement actuator and force sensor hybridization using a thick-film double-paste printing method 421
H. Moilanen, J. Lappalainen, L. Laitinen and S. Leppävuori (Oulu, Finland)

Acceleration sensor with integrated compensation of temperature effects fabricated by the LIGA process 426
M. Strohrmann, P. Bley, O. Fromhein and J. Mohr (Karlsruhe, Germany)

Thermal behaviour of CMOS Hall sensors for different operating modes 430
R. Gottfried-Gottfried (Dresden, Germany)

Ceramic pressure sensor based on tantalum thin film 435
I. Ayerdi, E. Castaño, A. Garcia-Alonso and F.J. Gracia (San Sebastián, Spain)

Elsevier Sequoia

A thick-film pressure transducer for cars propelled by natural gas 439
L. Fraigi, D. Lupi and L. Malatto (San Martin, Buenos Aires, Argentina)

Magnetometric sensor based on anhysteretic processes 442
A. García, E. López, C. Aroca, P. Sánchez and M.C. Sanchez (Madrid, Spain)

Calibration of three-axial rate gyros without angular velocity standards 446
F. Ferraris, I. Gorini, U. Grimaldi and M. Parvis (Turin, Italy)

High-performance Hall sensors based on III–V heterostructures 450
V. Mosser, S. Aboulhouda, J. Denis (Montrouge, France), S. Contreras, Ph. Lorenzini, F. Kobbi and J.L. Robert (Montpellier, France)

Mechanical limitations in the performance of integrated acoustic sensors 455
R.N. Tait and A.W. Mitchell (Edmonton, Alta., Canada)

A novel model for the temperature characteristic of a thick-film piezoresistive sensor 460
R.P. Sion, J.K. Atkinson and J.D. Turner (Southampton, UK)

On the use of quartz crystal capacitive dependence for measurement of 0–1 ml volumes 465
V. Matko, D. Đonlagić and J. Koprivnikar (Maribor, Slovenia)

Comparison of the mass sensitivity of Love and Rayleigh waves in a three-layer system 472
J. Enderlein, E. Chilla and H.-J. Fröhlich (Berlin, Germany)

Ultrasonic sensor system for characterization of liquid systems 476
B. Henning (Barleben, Germany), R. Lucklum, B. Kupfernagel (Magdeburg, Germany) and P. Hauptmann (Barleben, Germany and Magdeburg, Germany)

Optimization of beam patterns for acoustic array sensors. 481
D. Ruser (Gdańsk, Poland)

Characterization and performance of BGO crystals for positron emission tomography 487
G. Gervino and E. Monticone (Turin, Italy)

Optical and Radiation Sensors

Thermoelectric radiation microsensors. 493
T. Elbel (Hannover, Germany), S. Poser and H. Fischer (Jena, Germany)

A low background, large solid angle neutron detector for spectroscopy and dosimetry application 497
G. Gervino, E. Monticone and A. Lavagno (Turin, Italy)

Hygrometer with fibre optic dew point detector 503
R.S. Jachowicz and D. Zalewski (Warsaw, Poland)

Position-sensitive photodetector with rectifying voltage–current characteristics 508
A. Medvíd' and Yu. Blums (Riga, Latvia)

Application of an infrared sensor for laser soldering process control 511
J. Nicolics, L. Musiejovsky and D. Schrottmayer (Vienna, Austria)

Optical restrictions on the quantitative use of grating coupler sensors (GCS) 516
P.K. Spohn (Zurich, Switzerland)

Chemical detection using pulse narrowing in evanescent wave sensors 525
V. Ruddy and J. Maguire (Dublin, Ireland)

Optimization and performance of a specifically coated intrinsic optical-fibre sensor for the detection of alkane compounds 529
C. Ronot, H. Gagnaire, J.P. Goure (Saint Etienne, France), N. Jaffrezic-Renault (Ecully, France) and T. Pichery (La Plaine Saint Denis, France)

PLZT pyroelectric radiant energy sensor. 535
A.H. Łoziński (Gdańsk, Poland)

A fully CMOS-compatible infrared sensor fabricated on SIMOX substrates 538
M. Müller, R. Gottfried-Gottfried, H. Kück (Dresden, Germany) and W. Mokwa (Duisburg, Germany)

Fiber optic sensor for oxygen determination in liquids. 542
E. Singer, G.L. Duveneck, M. Ehrat and H.M. Widmer (Basle, Switzerland)

A multi-purpose sensor based on surface plasmon polariton resonance in a Schottky structure 547
P.I. Nikitin and A.A. Beloglazov (Moscow, Russian Federation)

The optimization of low cost integrated pyroelectric sensor arrays 553
D. Lienhard, S. Nitschke, B. Ploss, W. Ruppel (Karlsruhe, Germany) and W. von Münch (Stuttgart, Germany)

Shallow p^+n junction silicon nuclear radiation detectors 558
J. Dobrovodský (Bratislava, Slovak Republic), I. Bešše (Piešťany, Slovak Republic), L. Hrubčín and P. Kováč (Bratislava, Slovak Republic)

Optical fiber sensor array for dynamic variables 562
J. Niewisch and H. Bartelt (Erlangen, Germany)

Technologies and New Materials

Tandem-photolithography process for thin-film sensors and micromechanics 569
H. Sachse and K. Bethe (Braunschweig, Germany)

Novel extra-accurate method for two-sided alignment on silicon wafers 573
S. Tatić-Lučić and Y.-C. Tai (Pasadena, CA, USA)

Reduction of heat loss of silicon membranes by the use of trench-etching techniques 578
J. Werno, R. Kersjes, W. Mokwa and H. Vogt (Duisburg, Germany)

CMOS-compatible integration of thin ferromagnetic films 582
B. Sauer, R. Gottfried-Gottfried, T. Haase and H. Kück (Dresden, Germany)

Application of VDF/TrFE copolymer for pyroelectric image sensors 585
D. Setiadi, P.P.L. Regtien and P.M. Sarro (Delft, Netherlands)

A novel thick-film technique, gravure offset printing, for the realization of fine-line sensor structures 593
S. Leppävuori, J. Väänänen, M. Lahti, J. Remes and A. Uusimäki (Oulu, Finland)

Software, Intelligent Sensors

Building the knowledge base of a production system from the raw data of a multi-sensor system 599
L.J. Barrios, A. Ruiz, P. Bustos and A. Ibañez (Arganda del Rey Madrid, Spain)

Hierarchy of structures of intelligent transducers 604
J. Kwasniewski (Cracow, Poland)

The characterization and compensation through sensor array signal processing techniques of drift and low frequency noise in thick-film semiconductor sensors 607
J.K. Atkinson, R.P. Sion and E. Sizeland (Southampton, UK)

A versatile computer controlled measuring system for recording voltage–current characteristics of various resistance sensors 612
D. Stanković and M. Zlatanović (Belgrade, Yugoslavia)

Fundamentals

Hall effect measurements to calculate the conduction control in semiconductor films of SnO_2 619
M.C. Horrillo, J. Gutiérrez, L. Arés, J.I. Robla, I. Sayago, J. Getino and J.A. Agapito (Madrid, Spain)

Thermodynamic stability of the operation of sensors 622
I. Kirschner (Budapest, Hungary)

Vibrating piezoelectric sensors 630
V.M. Mecea (Cluj-Napoca, Romania)

Modelling aspects of surface acoustic wave gas sensors 638
P.A. Banda, W.B. Wlodarski and J.R. Scott (Melbourne, Vic., Australia)

Modelling of oscillating quartz sensors and related structures 643
H.M. Reuther, M. Weinmann, M. Fischer, W. von Münch and F. Assmus (Stuttgart, Germany)

New results on optical pressure sensors based on semiconductor quantum wells 654
T.P. Sosin, P. Perlin, W. Trzeciakowski (Warsaw, Poland), R. Tober (Adelphi, MD, USA) and R. Żarecka (Warsaw, Poland)

Nano-technologies, Micromachining

Piezoelectric position sensor for ultrasonic EFM motors 661
G.-A. Racine, R. Luthier and N.F. de Rooij (Neuchâtel, Switzerland)

A silicon–silicon nitride membrane fabrication process for smart thermal sensors 666
P.M. Sarro, A.W. van Herwaarden and W. van der Vlist (Delft, Netherlands)

Mechanical analysis of polycrystalline and single-crystalline silicon microstructures 672
A. Kovács and A. Stoffel (Furtwangen, Germany)

Thermally driven micromechanical bridge resonators 680
C. Burrer and J. Esteve (Bellaterra, Barcelona, Spain)

Sputtered silicon thin films for piezoresistive pressure microsensors 685
I. Obieta and F.J. Gracia (San Sebastián, Spain)

Preparation and characterization of ultrathin crystalline silicon membranes 689
B. Schmidt, J. von Borany, U. Todt and A. Erlebach (Dresden, Germany)

A phase-modulating microphone utilizing integrated optics and micromachining in silicon 695
U. Schneider and R. Schellin (Darmstadt, Germany)

Author Index of Volumes A41 and A42 699

Subject Index of Volumes A41 and A42 701

The publisher encourages the submission of articles in electronic form thus saving time and avoiding rekeying errors. A leaflet describing our requirements is available from the publisher upon request.